

Report Number: PL18100-001A
Model: OSQP-C-3L-57K7-3R-UL (Light Engine)
Issue Date: 01/04/2024

Cree Racine Engineering Services Testing Laboratory (RESTL) Photometric Testing and Evaluation Report

Prepared For:

Tammy Lehrmann

Cree Lighting

9201 Washington Avenue

Racine, WI 53406

Prepared By:



Meranda Hubbard, Photometric Test Technician

Approved By:



Jonathan Vollers, Technical Manager

Product Information

Manufacturer	Cree Lighting
Model Number (SKU)	OSQP-C-3L-57K7-3R-UL (Light Engine)
Serial Number	18100
LED Type	SSC STW7C12C-E0

Product Description

OSQP-C Pathway Luminaire (Light Engine), 3L Lumen Package, 5700K 70CRI, Type 3M Rotatable Optics

Driver Information (Where Applicable)

Signify XI030C080V054BSJ1

Length	Width	Height
9.5"	9.5"	6.9"

Sample

The following sample was submitted for evaluation



Key Photometric Data	Sphere Output	Goniophotometer	
Luminous Flux	2795.1	2869.0	lm
Efficacy	142.20	145.71	lm/W
Correlated Color Temperature (CCT)	5965	K	
Color Rendering Index (CRI)	73		
R ₉	-28		
Duv	0.0007		
TM-30 R _f *	73		
TM-30 R _g *	94		
TM-30 R _{cs,h1} *	-18.0%		
S/P Ratio*	1.96		

	Sphere		Goniophotometer		
Electrical Measurements	120V	277V	120V	277V	
Input Wattage	19.66	19.82	19.69	19.79	W
Input Current	0.169	0.075	0.169	0.075	A
Input Voltage	120.07	277.16	120.18	277.3	V
Power Factor	0.967	0.957	0.971	0.958	
Off-State Power	0	0	0	0	W
Total Harmonic Distortion (Voltage)	0.18	0.09	0.05	0.10	%
Total Harmonic Distortion (Amperage)	12.33	10.61	11.83	10.02	%

Note: All photometric measurements taken at 120VAC.

Luminous Intensity Distribution	Goniophotometer	
Max Candela	1616.805	Cd
Angle of Max Candela (Horizontal)	60	°
Angle of Max Candela (Vertical)	62	°

Key Test Parameters	Sphere Output	Goniophotometer	
Stabilization Time	59	33	min
Total Operating Time (Stabilization + Test)	69	53	min
Ambient Temperature	24.06	25.2	°C


Chromaticity Coordinates

x	y	u	v	u'	v'	Duv
0.3227	0.3336	0.2030	0.3148	0.2030	0.4722	0.0007

Color Rendering Index Details

Ra	R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14
73	71	78	80	74	72	68	82	60	-28	45	71	40	72	89

Chromaticity Diagram



NOTE: The Chromaticity Diagram shown above references table A1 specification for 7-step quadrangles referenced in ANSI C78.377-2017.

Spectral Distribution


λ (nm)	W/nm
360	0.000021
370	0.000007
380	0.000025
390	0.000096
400	0.000101
410	0.000619
420	0.003790
430	0.016143
440	0.044852
450	0.103033
460	0.048447
470	0.022220
480	0.009987
490	0.009299
500	0.016209
510	0.027668
520	0.037110

λ (nm)	W/nm
530	0.042145
540	0.044214
550	0.045288
560	0.046057
570	0.046400
580	0.045459
590	0.043062
600	0.039052
610	0.034031
620	0.028568
630	0.023285
640	0.018493
650	0.014411
660	0.011069
670	0.008321
680	0.006217
690	0.004631

λ (nm)	W/nm
700	0.003436
710	0.002540
720	0.001883
730	0.001373
740	0.001003
750	0.000732
760	0.000539
770	0.000392
780	0.000294
790	0.000201
800	0.000147
810	0.000104
820	0.000082
830	0.000062


Dominant Wavelength	491	nm
Peak Wavelength	451	nm

Spectral Power Distribution (W/nm)




Zonal Lumen Summary

Zone	Lumens	% of Total	Zone	Lumens
0-20	240.3	8.4	0-10	64.3
0-30	509.6	17.8	10-20	176.0
0-40	884.9	30.8	20-30	269.4
0-60	2020.8	70.4	30-40	375.3
0-80	2831.9	98.7	40-50	501.2
0-90	2868.7	100.0	50-60	634.7
10-90	2804.5	97.8	60-70	567.9
20-40	644.6	22.5	70-80	243.2
20-50	1145.8	39.9	80-90	36.9
40-70	1703.9	59.4	90-100	0.0
60-80	811.1	28.3	100-110	0.0
70-80	243.2	8.5	110-120	0.0
80-90	36.9	1.3	120-130	0.0
90-110	0.0	0.0	130-140	0.0
90-120	0.0	0.0	140-150	0.0
90-130	0.0	0.0	150-160	0.0
90-150	0.0	0.0	160-170	0.0
90-180	0.0	0.0	170-180	0.0
110-180	0.0	0.0		
Total	2868.7 lm	100%		



Roadway Summary	Lumens	% Lamp
Distribution	TYPE III SHORT	
Downward Street Side	1984.9	69.2
Downward House Side	883.9	30.8
Downward Total	2868.8	100.0
Upward Street Side	0.0	0.0
Upward House Side	0.0	0.0
Upward Total	0.0	0.0
Total Lumens	2868.8	100.0

Luminaire Classification System (LCS)	Lumens	% Luminaire
FL - Front Low (0-30)	307.2	10.7
FM - Front Medium (30-60)	1043.4	36.4
FH - Front High (60-80)	609.7	21.3
FVH - Front Very High (80-90)	24.6	0.9
BL - Back Low (0-30)	202.4	7.1
BM - Back Medium (30-60)	467.8	16.3
BH - Back High (60-80)	201.4	7.0
BVH - Back Very High (80-90)	12.2	0.4
UL - Uplight Low (90-100)	0.0	0.0
UH - Uplight High (100-180)	0.0	0.0
BUG Rating*	B1-U0-G1	



Candela Tabulations

	0	5	10	15	20	25	30	35	40	45	50	55	60	65	70
0	702.1	702.1	702.1	702.1	702.1	702.1	702.1	702.1	702.1	702.1	702.1	702.1	702.1	702.1	702.1
1	708.6	711.3	711.3	711.1	711.9	712.2	712.2	711.7	710.8	710.8	709.1	708.3	706.9	706.3	704.8
2	716.9	719.8	719.7	719.2	719.7	719.9	719.3	718.7	717.3	716.9	714.7	713.2	711.3	709.8	707.6
3	723.8	726.5	726.4	725.8	726.2	726.2	725.2	724.3	722.5	721.5	719.1	717.1	714.9	712.7	709.7
4	729.2	732.0	732.0	731.3	731.3	731.2	730.2	729.0	726.9	725.5	722.5	720.0	717.6	714.8	711.4
5	734.3	737.1	736.8	736.1	735.8	735.6	734.3	733.0	730.5	728.9	725.6	722.7	719.8	716.4	712.4
6	738.1	740.9	740.7	739.9	739.5	739.3	737.8	736.5	733.8	731.7	728.2	724.8	721.2	717.4	712.8
7	741.9	744.7	744.4	743.7	743.2	742.8	741.0	739.3	736.1	733.6	730.0	726.1	722.0	717.9	712.8
8	745.2	748.0	747.6	746.9	746.4	745.8	743.9	741.8	738.4	735.3	731.1	727.0	722.7	718.1	712.6
9	748.3	751.0	750.8	750.0	749.3	748.5	746.4	743.9	740.4	736.9	732.2	727.8	723.0	717.9	712.1
10	751.0	753.6	753.5	752.6	752.0	750.7	748.6	745.7	741.8	738.2	733.3	728.4	722.9	717.6	711.1
11	753.9	756.6	756.3	755.4	754.5	752.9	750.5	747.5	743.5	739.4	734.1	728.8	722.8	717.0	710.0
12	756.7	759.3	759.0	758.1	756.9	755.2	752.5	749.3	744.9	740.6	734.8	729.3	722.7	716.3	708.6
13	759.0	761.4	761.5	760.7	759.6	757.8	754.8	751.2	746.5	741.8	735.6	729.5	722.4	715.2	706.9
14	760.1	762.8	762.8	762.1	761.3	760.0	757.0	753.2	748.1	743.2	736.5	729.7	722.0	714.1	704.8
15	760.7	763.4	763.6	763.0	762.3	761.2	758.6	755.1	750.0	744.7	737.5	730.1	721.5	712.9	702.8
16	760.5	763.3	763.6	763.3	763.0	762.2	759.9	756.7	751.7	746.1	738.5	730.5	721.0	711.6	700.6
17	760.9	763.8	764.2	763.8	763.3	762.9	761.0	757.8	753.1	747.5	739.5	730.9	720.6	710.2	698.4
18	761.6	764.5	764.8	764.5	764.0	763.5	761.7	758.8	754.3	748.8	740.5	731.2	720.2	708.6	695.9
19	762.4	765.0	765.4	765.0	764.5	764.1	762.4	759.6	755.3	749.7	741.2	731.5	719.4	706.9	693.1
20	762.4	765.3	765.8	765.5	765.0	764.7	763.4	760.2	755.9	750.3	742.0	731.5	718.7	705.1	690.4
21	762.6	765.4	765.8	765.7	765.5	765.5	764.2	761.5	756.8	751.3	742.5	731.6	718.1	703.4	687.4
22	763.3	765.9	766.3	766.1	766.1	766.7	765.4	762.8	758.3	752.4	743.2	731.9	717.6	702.0	685.0
23	764.6	767.2	767.6	767.2	767.3	767.9	767.0	764.5	760.0	753.8	744.1	732.5	717.4	701.0	682.5
24	766.5	769.1	769.6	769.3	769.2	769.6	769.0	766.4	762.2	755.8	745.8	733.8	717.9	700.4	680.8
25	768.3	771.2	771.8	771.7	772.0	772.2	771.5	768.7	764.6	758.3	747.9	735.4	718.9	700.3	679.1
26	770.4	773.2	773.9	773.9	774.8	775.3	774.8	771.8	767.2	761.2	750.6	737.7	720.4	700.6	678.2
27	772.2	775.2	776.0	776.3	777.3	778.6	778.5	775.3	770.4	764.3	753.7	740.6	722.6	701.3	677.7
28	774.0	777.1	777.8	778.6	780.3	781.9	782.2	779.3	774.2	767.7	757.2	743.9	725.1	702.5	677.6
29	776.4	779.5	780.4	781.3	783.6	785.5	786.1	783.4	778.6	771.7	761.1	747.4	728.0	704.3	678.1
30	778.9	782.4	783.4	784.6	787.0	789.6	790.3	788.1	783.5	776.4	765.3	751.5	731.6	706.6	679.5
31	782.1	785.8	787.0	788.3	791.1	794.3	794.8	793.3	789.0	781.9	770.1	756.1	735.4	709.8	681.5
32	785.7	789.4	790.7	792.4	795.7	799.1	800.2	799.0	795.2	788.1	775.8	761.1	739.6	713.6	684.2
33	789.3	793.2	795.0	797.1	800.8	804.7	806.1	805.0	801.7	794.5	782.1	766.3	744.6	718.1	687.6
34	793.2	797.1	799.5	802.5	806.8	811.3	813.0	812.2	809.1	801.7	789.2	772.5	750.0	723.2	691.9
35	797.2	801.2	804.4	808.1	813.4	818.5	820.9	820.2	817.5	809.9	797.0	779.8	756.3	729.1	697.1
36	801.6	805.9	809.3	814.3	820.8	826.8	829.5	829.6	826.9	819.0	805.6	788.0	763.5	735.9	703.4

Candela Tabulations (Continued)

	75	80	85	90	95	100	105	110	115	120	125	130	135	140	145
0	702.1	702.1	702.1	702.1	702.1	702.1	702.1	702.1	702.1	702.1	702.1	702.1	702.1	702.1	702.1
1	703.6	702.6	700.3	700.3	698.5	698.9	698.3	697.7	697.4	696.3	696.1	695.0	695.2	694.2	693.4
2	705.6	703.8	700.5	699.6	697.0	696.3	694.6	692.6	691.3	688.9	687.6	685.3	683.9	682.2	680.5
3	706.9	704.3	700.2	698.4	694.8	692.9	690.1	686.8	684.1	680.1	677.5	673.8	670.9	668.0	664.8
4	707.8	704.5	699.5	696.8	692.3	689.2	685.1	680.2	675.8	670.4	665.9	660.9	655.7	651.6	647.2
5	708.2	704.3	698.4	694.8	689.4	684.9	679.4	673.2	666.7	659.5	653.0	646.8	640.1	634.6	629.3
6	708.1	703.5	696.9	692.5	686.1	680.3	673.3	665.6	656.9	647.9	639.7	632.4	624.2	616.8	610.5
7	707.5	702.4	695.1	689.8	682.5	675.4	666.8	657.1	646.5	636.3	626.1	617.5	608.0	599.0	592.0
8	706.7	700.9	693.0	687.1	678.6	670.0	659.9	648.5	635.9	623.8	612.5	602.1	591.6	581.4	574.1
9	705.6	699.2	690.3	683.6	674.3	664.1	652.2	639.2	625.1	611.5	598.3	586.7	575.4	564.5	556.2
10	704.2	697.1	687.5	680.0	669.4	657.9	644.2	629.4	613.9	598.5	583.8	571.4	559.8	547.9	539.3
11	702.6	694.8	684.4	676.2	664.4	651.5	635.9	619.6	602.5	585.5	569.9	556.1	544.2	532.9	524.5
12	700.7	692.3	681.2	672.2	659.2	645.1	627.6	609.6	591.3	572.7	556.2	541.5	529.8	518.9	510.6
13	698.4	689.2	677.6	667.6	653.5	638.0	619.0	599.4	579.6	560.0	542.8	527.7	516.5	506.1	497.7
14	695.6	686.0	673.6	662.7	647.7	630.7	610.2	588.9	567.9	547.7	530.1	515.2	504.5	494.0	485.1
15	692.9	682.5	669.2	657.6	641.7	623.4	601.4	578.4	556.4	535.9	518.4	504.0	492.9	482.3	472.9
16	689.7	678.7	664.7	652.5	635.4	615.9	592.4	567.8	545.1	524.5	507.5	493.4	481.6	470.8	461.2
17	686.4	674.5	659.8	646.8	628.8	608.0	583.2	557.2	534.2	514.1	497.2	483.0	470.9	459.6	450.0
18	682.8	670.4	654.7	640.8	622.2	599.8	573.5	547.0	524.3	504.2	487.4	473.1	460.4	449.0	439.2
19	679.2	666.1	649.4	634.6	615.1	591.2	564.2	537.7	514.8	494.7	478.1	463.6	450.6	438.8	428.9
20	675.7	661.4	644.0	628.3	607.7	582.6	555.0	528.7	505.7	485.6	468.7	454.3	441.0	429.1	418.6
21	671.8	656.5	638.4	622.0	599.9	574.1	546.5	520.2	496.8	476.8	459.6	445.1	431.8	419.4	408.5
22	668.1	651.7	633.0	615.5	592.6	566.1	538.4	512.1	488.6	468.6	451.2	436.7	423.2	410.2	399.3
23	664.5	647.2	627.9	609.1	585.5	558.7	531.2	504.6	481.0	461.0	443.8	428.9	414.8	401.6	390.7
24	661.4	643.3	622.9	602.9	578.9	552.1	524.2	497.6	474.1	454.2	437.0	421.6	407.0	393.6	383.6
25	658.9	639.6	618.2	597.5	572.8	546.0	517.9	491.4	468.0	448.2	431.0	414.8	399.8	386.8	378.3
26	657.0	636.5	614.2	592.7	567.6	540.7	512.2	485.8	462.7	443.0	425.4	408.5	393.5	381.6	374.8
27	655.4	633.9	610.5	588.3	563.0	535.7	507.0	480.9	458.1	438.6	420.4	402.5	388.0	377.9	372.1
28	654.2	631.6	607.3	584.7	558.9	531.4	502.5	476.8	454.2	434.8	415.7	397.1	383.5	374.9	370.6
29	653.5	629.9	604.8	581.8	555.7	527.7	498.7	473.2	451.1	431.4	411.2	392.6	380.3	372.9	370.4
30	653.4	628.7	603.0	580.0	553.1	524.8	495.7	470.3	448.7	428.1	407.2	389.2	378.0	372.3	371.9
31	654.2	628.4	602.2	578.8	551.3	522.5	493.2	468.2	446.8	425.0	403.8	386.9	377.0	373.2	374.8
32	655.8	628.8	602.3	578.5	550.2	520.9	491.4	466.7	445.1	422.2	401.2	385.7	377.6	375.8	378.9
33	658.2	630.1	603.2	579.1	549.9	520.0	490.1	465.9	443.9	419.8	399.7	385.5	379.8	379.5	383.5
34	661.3	632.3	605.4	580.7	550.8	519.7	489.9	465.5	442.9	418.2	399.0	386.8	382.8	383.7	387.5
35	665.7	636.1	608.4	583.2	552.6	520.3	490.2	465.9	442.4	417.4	399.5	389.2	386.4	388.0	391.1
36	670.8	640.7	612.5	586.8	555.4	521.9	491.3	467.4	442.7	417.7	401.1	392.4	390.7	391.1	394.4

Candela Tabulations (Continued)

	150	155	160	165	170	175	180
0	702.1	702.1	702.1	702.1	702.1	702.1	702.1
1	692.8	690.9	690.6	688.8	688.8	688.4	685.1
2	679.0	676.1	675.0	672.8	672.2	671.5	667.2
3	662.2	657.9	655.9	653.3	651.9	650.9	646.2
4	643.6	638.7	635.8	632.8	631.2	630.1	624.6
5	624.7	619.2	615.3	611.6	609.4	608.4	602.3
6	605.0	599.2	594.1	590.4	587.9	586.7	580.7
7	585.5	579.7	573.6	570.1	566.9	565.7	560.1
8	566.7	561.0	554.2	550.3	547.1	545.9	541.8
9	548.4	542.9	536.8	532.7	529.9	528.9	525.4
10	532.0	526.8	521.2	516.9	514.4	513.2	510.3
11	517.4	512.0	506.8	502.2	499.7	498.3	495.7
12	503.6	497.9	493.0	488.4	485.6	484.3	481.5
13	490.6	484.5	479.5	474.6	471.9	470.5	467.5
14	477.7	471.1	466.2	461.3	458.4	457.0	454.0
15	465.4	458.3	453.3	448.8	445.8	444.2	441.0
16	453.6	446.1	441.2	436.6	433.4	431.8	428.3
17	442.1	434.6	429.1	424.6	421.0	419.2	415.5
18	431.0	423.0	417.1	412.7	409.1	407.0	403.2
19	420.1	411.8	405.6	401.3	397.6	396.0	392.3
20	409.1	401.1	394.7	390.3	387.3	386.0	382.9
21	398.6	391.2	385.1	381.4	379.0	378.0	375.8
22	389.1	382.4	377.5	374.7	373.3	372.9	371.5
23	381.4	375.9	372.4	370.7	370.0	369.9	368.9
24	376.1	371.9	369.2	368.5	368.4	368.9	368.0
25	372.4	369.0	367.5	368.0	368.9	369.7	369.3
26	369.9	367.8	367.5	369.1	371.0	372.0	371.6
27	368.8	368.2	369.1	371.6	374.3	375.5	375.1
28	369.4	370.2	372.0	375.2	378.5	379.9	379.9
29	371.6	374.1	376.7	379.9	383.1	384.8	384.7
30	375.0	379.6	382.4	385.1	388.0	389.5	389.4
31	379.4	385.2	388.3	390.3	393.2	394.2	394.0
32	384.5	389.8	393.8	395.9	398.6	399.0	398.0
33	388.7	394.1	399.0	401.4	403.2	402.6	400.6
34	392.8	398.7	403.4	405.6	406.0	404.5	401.6
35	397.1	402.5	406.3	407.0	406.3	404.0	400.4
36	400.9	405.4	407.2	405.9	403.9	401.3	397.4

Candela Tabulations (Continued)

	0	5	10	15	20	25	30	35	40	45	50	55	60	65	70
37	806.6	811.3	815.1	820.6	828.6	835.5	839.4	839.7	836.7	829.1	815.0	797.3	771.7	743.6	710.2
38	812.5	817.4	821.5	827.4	836.9	845.1	849.9	850.6	848.0	840.3	825.4	807.2	780.9	751.6	718.1
39	819.3	824.2	828.8	834.9	846.0	855.4	861.3	862.6	860.3	852.2	837.0	817.8	790.9	760.4	727.0
40	826.4	831.3	836.7	843.0	855.2	865.9	872.9	876.3	874.6	866.2	849.5	829.8	802.1	770.3	737.2
41	833.7	839.2	845.5	851.8	865.2	878.5	887.5	891.0	889.0	881.8	864.7	843.3	814.5	781.7	748.3
42	841.8	847.2	854.3	860.8	875.6	891.3	901.0	905.7	904.3	898.2	881.1	858.6	828.3	794.3	761.3
43	848.8	855.1	863.2	870.5	887.0	903.5	915.2	921.0	920.9	915.2	899.0	876.2	844.5	808.5	775.6
44	854.4	862.1	871.1	879.6	896.8	915.6	929.7	937.6	938.7	933.7	918.5	894.9	862.5	824.8	791.8
45	859.5	868.2	877.7	889.6	906.5	927.6	944.5	954.7	957.6	953.4	940.1	916.6	882.0	845.3	810.1
46	863.4	872.7	883.3	897.3	915.1	938.8	959.1	972.6	977.0	974.7	963.4	940.5	904.2	866.8	832.4
47	865.2	875.1	886.9	902.6	921.8	948.8	975.0	990.0	998.6	998.8	988.3	967.1	929.3	890.7	855.5
48	864.7	874.9	888.1	905.7	927.1	956.6	988.0	1006.4	1018.8	1022.6	1017.4	995.8	957.9	918.1	881.1
49	861.4	871.7	886.6	905.8	930.2	962.6	998.4	1022.6	1039.4	1047.8	1046.3	1029.8	991.3	949.8	911.3
50	855.7	865.7	881.7	903.2	930.0	965.5	1005.5	1036.1	1059.2	1073.3	1077.0	1067.4	1028.6	986.8	945.8
51	846.2	856.2	873.8	897.0	926.1	965.6	1010.1	1047.2	1077.3	1100.3	1110.4	1108.8	1074.8	1028.7	984.2
52	833.7	843.4	861.8	886.6	917.4	958.8	1010.4	1055.8	1095.1	1127.0	1146.4	1154.1	1125.4	1079.0	1027.7
53	817.6	826.9	846.1	870.0	904.2	949.4	1006.3	1060.9	1109.8	1154.7	1185.7	1204.9	1181.2	1131.7	1077.0
54	797.6	806.2	825.7	850.1	887.2	935.6	997.5	1061.3	1122.1	1181.1	1227.6	1257.6	1240.2	1187.0	1126.1
55	773.1	780.6	799.1	826.2	863.0	917.5	984.5	1057.8	1131.4	1206.2	1269.6	1311.4	1302.0	1245.5	1176.6
56	745.1	750.4	769.0	798.0	836.6	894.3	965.8	1048.4	1135.5	1227.5	1311.9	1366.7	1364.8	1304.5	1227.4
57	711.9	716.4	734.8	764.9	806.6	865.7	941.4	1033.8	1133.8	1244.3	1349.6	1419.5	1425.8	1361.3	1274.5
58	672.6	677.8	696.1	727.4	771.4	833.9	912.6	1011.7	1126.5	1255.2	1383.0	1468.9	1481.0	1415.1	1315.1
59	626.8	633.8	653.6	684.2	732.1	798.6	877.3	984.0	1112.0	1260.2	1410.0	1513.3	1531.4	1461.6	1349.3
60	576.4	585.4	606.6	637.4	687.9	758.2	837.8	949.7	1091.0	1257.0	1427.3	1548.8	1572.1	1501.1	1374.0
61	522.5	531.8	554.9	586.4	639.8	712.2	793.2	910.0	1062.2	1245.2	1434.6	1572.7	1601.4	1527.0	1389.0
62	467.7	473.4	497.1	531.5	585.4	660.6	742.3	862.8	1025.7	1223.3	1431.5	1584.3	1616.8	1539.3	1393.5
63	410.9	414.0	437.5	473.0	526.8	602.5	687.9	812.2	980.5	1192.0	1415.3	1578.3	1616.2	1534.7	1385.1
64	357.2	358.6	380.4	413.9	465.6	540.8	628.9	756.1	929.5	1146.5	1382.6	1555.3	1597.0	1515.1	1365.9
65	309.9	310.8	330.1	359.7	405.3	477.9	565.6	692.6	869.3	1091.4	1335.6	1514.8	1560.2	1479.8	1332.4
66	270.0	270.8	286.8	312.8	351.0	416.5	500.8	626.0	803.5	1027.6	1277.5	1459.8	1507.8	1428.8	1285.7
67	236.0	237.0	250.3	272.4	303.9	361.2	439.7	560.6	734.6	953.5	1205.1	1392.7	1441.7	1365.5	1225.2
68	207.3	208.8	219.0	238.7	264.7	312.5	384.8	497.0	664.8	872.2	1119.3	1311.4	1364.1	1292.6	1156.7
69	184.2	185.5	194.2	210.2	231.6	271.6	335.9	437.4	593.0	786.7	1023.2	1219.6	1274.7	1210.1	1078.3
70	167.0	168.1	175.0	187.3	205.0	237.4	292.2	382.8	522.0	697.3	919.9	1119.6	1177.7	1115.5	996.9
71	153.6	154.5	159.6	168.9	183.9	207.9	253.9	332.4	454.3	609.7	814.9	1013.1	1073.0	1020.4	910.2
72	141.0	142.1	146.2	153.7	165.8	184.0	221.1	287.3	391.8	526.3	705.4	899.0	964.8	920.9	820.5
73	128.6	130.3	133.9	139.5	150.0	165.2	193.6	247.7	336.1	446.5	601.1	782.2	858.8	822.6	736.3

Candela Tabulations (Continued)

	75	80	85	90	95	100	105	110	115	120	125	130	135	140	145
37	677.1	646.4	617.5	591.6	559.3	524.4	493.3	469.6	443.5	419.1	403.9	396.6	395.2	393.8	397.8
38	684.6	653.5	623.9	597.6	564.2	527.9	496.3	472.3	444.8	421.4	407.5	401.4	398.8	396.8	400.9
39	693.3	661.9	631.5	604.9	570.1	532.3	500.0	475.6	446.8	424.8	411.9	405.8	401.5	399.5	402.0
40	703.2	671.9	640.4	613.2	577.1	537.5	504.4	479.1	449.7	429.1	416.8	408.7	404.1	401.2	401.1
41	714.4	682.6	650.8	622.7	585.3	543.5	509.5	483.2	453.3	434.1	421.7	410.9	405.9	401.1	398.5
42	727.0	695.0	663.1	634.1	594.8	550.4	515.5	487.6	457.8	440.1	425.9	412.6	406.2	399.9	393.9
43	741.1	708.8	677.0	647.2	605.6	558.3	522.0	492.1	463.0	445.4	428.9	414.0	405.6	396.7	387.9
44	757.2	724.8	693.1	661.3	617.0	566.9	529.0	496.9	468.1	449.3	430.7	414.8	404.0	392.1	380.3
45	776.1	742.9	711.0	677.6	629.7	576.1	536.1	501.6	472.9	452.1	430.6	413.8	400.7	386.2	370.2
46	797.2	763.3	730.6	695.1	643.3	585.8	543.5	506.3	477.1	453.4	429.2	411.0	396.5	378.1	358.0
47	822.5	785.6	752.4	713.6	657.1	595.4	550.4	510.4	480.3	453.0	426.3	407.4	390.1	367.5	344.6
48	848.3	812.1	775.8	732.9	670.9	604.5	556.8	513.6	481.9	450.3	422.1	402.4	381.5	354.3	331.3
49	878.4	841.7	799.7	752.5	684.1	613.0	562.2	516.1	482.2	446.8	417.0	395.9	370.2	340.9	319.1
50	911.7	872.9	827.2	772.4	697.4	621.0	566.1	517.6	481.0	442.5	411.5	385.9	356.2	327.8	308.7
51	948.5	906.7	854.2	792.7	710.6	628.6	568.9	517.6	477.8	436.6	403.7	371.1	340.3	317.6	300.2
52	988.3	942.9	883.2	816.0	723.0	635.1	570.6	516.1	472.7	428.2	390.7	353.8	327.8	310.8	293.6
53	1029.6	980.5	913.5	836.4	733.3	639.1	569.9	512.1	464.3	417.3	374.8	340.4	320.2	305.3	288.7
54	1072.1	1018.2	942.8	854.1	740.9	639.5	565.2	504.0	454.4	404.6	360.9	331.6	315.8	300.6	286.1
55	1115.4	1053.9	968.7	867.6	744.3	634.3	557.0	493.9	443.7	391.8	350.0	325.4	311.9	296.5	284.9
56	1156.1	1088.5	990.4	876.7	743.3	626.2	545.6	481.7	431.3	379.6	341.4	320.7	307.7	293.1	284.1
57	1192.3	1115.4	1006.2	880.2	737.7	614.7	530.1	467.1	417.0	368.2	334.0	316.9	303.3	290.9	282.9
58	1223.7	1137.1	1016.9	879.7	728.3	598.7	510.2	448.2	400.2	355.9	326.7	312.8	298.7	288.5	281.0
59	1247.2	1154.2	1024.3	875.8	716.3	577.5	485.5	425.5	381.1	342.0	319.1	307.6	294.3	285.6	277.9
60	1262.8	1164.7	1026.9	868.2	701.2	552.6	458.0	399.8	360.4	327.1	311.2	301.5	290.0	281.7	273.6
61	1270.8	1168.1	1022.1	853.7	682.2	523.7	426.9	372.9	338.4	311.1	301.9	294.4	285.2	277.2	268.8
62	1269.8	1163.6	1009.7	835.3	658.0	489.7	394.5	346.8	316.9	295.3	292.0	287.1	279.0	271.8	263.5
63	1257.4	1149.5	989.5	810.8	629.5	454.1	361.5	321.4	296.8	279.8	281.0	279.1	272.4	265.1	257.2
64	1234.8	1124.1	961.7	780.0	598.2	417.8	329.6	296.4	276.8	265.2	268.9	270.1	264.6	257.7	250.3
65	1201.3	1088.4	923.3	742.4	562.2	380.5	299.5	271.8	257.0	250.9	256.1	258.9	255.2	249.2	242.9
66	1155.6	1042.1	875.1	698.1	521.6	344.8	273.0	250.3	239.1	237.2	243.8	247.6	245.0	240.2	234.9
67	1099.9	981.6	817.8	648.4	477.7	312.6	249.1	230.5	223.3	224.1	231.6	236.2	233.9	230.5	226.5
68	1032.4	914.1	757.1	598.9	434.1	283.2	227.1	211.9	208.4	211.8	219.6	224.1	221.8	219.4	216.7
69	956.7	843.4	695.3	547.8	392.8	257.2	207.4	194.3	193.9	199.1	207.6	211.8	208.1	207.3	205.9
70	878.6	772.3	634.9	500.5	353.9	233.8	189.4	178.1	180.2	187.0	195.4	199.2	194.0	195.2	194.2
71	799.0	700.6	576.1	454.4	318.6	212.1	172.2	163.2	167.0	174.9	183.2	186.2	180.7	182.7	180.5
72	717.4	631.8	520.4	409.8	286.1	191.9	155.7	148.9	153.7	162.2	169.4	171.4	166.1	168.5	164.4
73	639.6	568.1	467.8	366.8	256.1	172.4	140.2	135.3	141.1	150.1	155.7	155.4	149.0	150.8	146.7

Candela Tabulations (Continued)

	150	155	160	165	170	175	180
37	403.5	406.1	405.8	402.7	399.1	395.9	391.5
38	404.2	404.5	401.8	397.1	392.0	387.8	383.5
39	403.1	400.5	395.6	388.9	382.6	377.7	373.1
40	399.6	394.3	386.7	378.4	371.2	365.7	361.2
41	394.1	385.5	375.5	365.7	358.0	351.8	346.9
42	386.9	374.6	362.4	351.3	342.2	335.3	330.0
43	377.6	362.2	348.0	335.0	324.9	317.8	312.2
44	366.1	347.9	332.2	318.2	307.2	300.9	295.6
45	352.8	333.1	316.5	301.8	291.0	286.0	282.0
46	338.8	318.8	301.2	287.7	278.9	275.3	272.1
47	325.0	305.8	288.3	276.8	270.6	268.2	266.6
48	312.0	294.5	279.0	270.5	266.1	264.5	263.1
49	300.8	285.7	272.9	266.1	262.1	260.7	259.1
50	292.0	279.2	268.7	262.5	258.4	256.7	254.9
51	285.2	274.6	265.9	259.4	255.1	252.9	251.2
52	280.5	271.7	263.6	256.7	252.1	249.3	247.7
53	278.0	269.7	261.4	254.5	249.1	246.2	244.4
54	276.9	267.9	259.1	252.2	246.4	243.2	241.1
55	276.1	266.1	256.9	249.5	243.4	240.2	237.6
56	274.7	264.2	254.6	246.7	240.4	237.0	234.6
57	272.9	261.9	251.8	244.0	237.4	233.9	232.2
58	270.6	259.2	248.7	241.2	235.1	232.0	230.9
59	267.3	255.8	245.8	238.7	233.3	230.7	230.1
60	262.8	251.3	242.1	236.7	231.9	229.8	229.0
61	257.4	246.0	237.3	233.6	230.3	228.5	225.8
62	251.8	240.4	232.2	229.9	227.6	226.5	223.7
63	245.9	235.4	228.0	226.0	223.3	221.5	218.7
64	239.8	230.0	223.7	220.7	217.5	212.0	208.1
65	233.4	224.4	217.5	213.6	209.8	199.6	193.3
66	227.1	217.9	208.6	204.8	200.6	187.9	180.9
67	220.0	208.3	198.8	195.8	189.9	178.0	171.3
68	211.3	196.9	188.9	185.6	176.3	167.2	159.9
69	199.6	184.1	178.0	170.1	158.4	151.1	143.6
70	185.5	170.8	162.6	152.3	139.6	132.4	125.9
71	170.3	156.6	146.7	134.7	121.9	114.6	109.6
72	154.1	143.2	132.3	119.2	108.1	102.8	99.4
73	138.5	130.9	118.5	106.4	98.1	93.7	90.7

Candela Tabulations (Continued)

	0	5	10	15	20	25	30	35	40	45	50	55	60	65	70
74	116.7	117.8	121.8	126.1	135.7	149.4	171.2	213.4	285.1	374.9	507.4	669.5	756.5	729.4	652.6
75	104.9	105.3	109.2	113.0	122.4	135.2	152.6	183.1	238.7	315.7	428.6	568.5	655.5	636.9	571.0
76	92.1	92.2	95.8	100.4	109.8	122.3	136.5	157.9	200.2	265.1	365.0	478.3	560.7	550.0	492.8
77	79.1	79.4	82.6	87.6	97.0	109.5	122.8	137.1	167.5	222.2	310.3	401.8	471.4	469.7	421.3
78	67.1	67.3	70.6	75.1	84.1	97.0	109.4	119.1	140.3	186.0	261.7	333.4	391.5	395.7	355.9
79	56.3	56.2	59.5	62.9	71.2	83.5	96.1	103.8	117.9	153.8	216.5	274.7	321.7	327.6	297.3
80	46.5	46.3	48.8	52.3	58.8	69.7	81.5	90.0	98.2	125.1	176.2	223.6	260.8	267.0	243.4
81	37.8	37.8	39.5	42.4	46.9	55.9	67.2	76.6	80.4	99.1	141.0	179.5	205.5	209.7	192.9
82	30.0	29.9	31.0	33.4	36.4	43.4	53.0	62.3	64.3	77.6	109.4	140.2	157.9	160.3	149.5
83	22.8	22.8	23.8	25.4	27.7	32.3	40.2	48.0	51.0	58.0	80.5	104.1	118.1	119.8	111.0
84	17.1	16.9	17.4	18.7	20.4	23.5	29.1	35.5	39.2	41.9	56.3	72.3	84.7	85.3	76.8
85	12.4	12.4	12.6	13.4	14.6	16.5	20.7	25.3	28.1	29.2	37.0	46.4	52.6	54.6	50.3
86	8.8	8.8	9.0	9.5	10.4	11.4	13.9	16.8	18.8	19.5	23.1	28.6	31.0	29.7	29.3
87	6.4	6.3	6.6	6.9	7.5	8.0	9.2	10.7	11.9	12.8	13.9	15.9	16.4	14.7	14.8
88	5.0	4.9	5.0	5.2	5.6	5.9	6.3	7.0	7.4	8.1	8.4	8.7	8.8	8.2	7.7
89	4.0	3.8	3.9	4.1	4.3	4.5	4.8	5.0	5.1	5.3	5.5	5.5	5.5	5.1	4.5
90	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Candela Tabulations (Continued)

	75	80	85	90	95	100	105	110	115	120	125	130	135	140	145
74	567.8	504.3	415.7	325.9	228.2	153.5	125.5	122.3	129.2	138.6	142.6	141.4	134.8	132.3	125.8
75	495.9	444.1	366.0	286.5	202.0	135.2	111.4	109.4	117.2	126.3	129.8	127.8	121.4	113.6	108.6
76	431.4	387.7	319.2	248.8	177.4	118.4	98.2	97.5	105.5	113.4	116.4	113.8	106.5	97.6	93.2
77	371.0	335.4	275.6	215.0	153.7	102.7	86.0	86.2	94.1	101.3	103.7	100.2	91.3	83.7	80.0
78	316.1	285.1	234.0	183.1	130.6	88.3	74.5	75.3	82.7	89.1	91.2	87.0	78.2	70.7	67.9
79	267.8	238.6	195.6	153.9	108.6	74.9	63.7	64.9	71.5	77.0	79.2	75.0	66.8	60.3	57.9
80	223.2	195.1	160.2	126.6	88.7	62.4	53.7	55.3	60.7	65.6	67.9	63.8	56.5	51.5	49.3
81	179.5	155.0	128.4	102.4	70.4	51.1	45.0	46.2	50.8	55.2	57.4	53.6	47.1	43.2	41.8
82	138.9	119.8	100.7	81.1	55.2	41.4	36.9	38.0	41.8	46.0	48.0	44.3	38.9	35.7	34.7
83	102.9	89.7	76.2	60.9	41.9	32.6	30.1	30.7	33.9	37.4	39.1	36.2	31.7	29.3	28.3
84	72.0	64.1	54.8	43.6	30.6	24.9	23.9	24.3	26.9	29.7	31.2	28.9	25.7	23.9	22.7
85	47.1	41.9	36.8	29.2	21.4	18.3	18.4	18.7	20.7	23.1	24.1	22.6	20.3	19.3	18.3
86	26.6	24.2	22.7	18.0	14.4	13.0	13.4	13.6	15.0	16.9	17.6	16.9	15.8	15.4	14.5
87	13.3	13.5	12.9	10.8	9.3	8.8	9.3	9.5	10.6	11.9	12.4	12.3	11.9	11.7	11.1
88	6.8	7.0	6.8	6.3	5.9	5.8	6.2	6.9	7.7	8.3	8.6	8.8	8.7	8.6	8.2
89	4.0	4.2	4.1	3.9	4.0	4.0	4.4	5.0	5.9	6.3	6.4	6.6	6.6	6.5	6.1
90	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Candela Tabulations (Continued)

	150	155	160	165	170	175	180
74	122.9	117.8	105.4	95.7	89.1	84.8	82.2
75	106.3	104.1	92.9	85.8	80.7	76.8	74.1
76	92.9	90.5	81.7	76.7	72.7	69.0	66.6
77	79.7	77.8	70.8	67.6	64.8	61.7	59.4
78	67.7	66.5	61.0	59.1	57.2	54.4	52.3
79	57.6	55.2	51.9	50.5	49.6	47.5	45.2
80	48.8	46.0	44.1	43.3	42.5	40.8	38.6
81	40.7	37.9	36.9	36.5	36.1	34.5	32.6
82	33.6	31.1	30.5	30.2	29.7	28.7	27.1
83	27.2	25.5	25.0	24.6	24.0	23.3	22.0
84	21.7	20.6	20.1	19.5	19.0	18.3	17.4
85	17.0	16.3	16.0	15.4	14.9	14.1	13.3
86	13.3	12.6	12.3	12.1	11.5	10.3	9.4
87	10.0	9.3	9.0	8.9	8.2	6.8	5.8
88	7.2	6.5	6.1	5.9	5.3	3.9	3.2
89	5.5	4.9	4.3	3.9	3.4	2.5	2.0
90	0.0	0.0	0.0	0.0	0.0	0.0	0.0

NOTE: The device under test emits no detectable uplight, as defined by ANSI/IES LM-75-19.

Test Date(s):

Equipment	Date
2M Sphere	01-03-2024
Type C Goniophotometer	01-04-2024

Integrating Sphere Equipment:

Description	Manufacturer	Model	Serial Number
2M Sphere	Labsphere	ILLUMIA PLUS 3020-195-4PI	1115184557
CCD Array Spectrometer	Labsphere	MC-9801:3683L	98010844
Lamp Power Supply	Labsphere	LPS-525-42	190615319
Programmable AC Source	Chroma	61602	616020003698
Power Analyzer	Xitron	XT2640	2641AD2006002

Goniophotometer Equipment:

Description	Manufacturer	Model	Serial Number
Type C Goniophotometer	LSI / UL	6440T	6440PN2028
Spectroradiometer	Gooch & Housego	770VIS/NIR	12415212
Spectrometer	Inphora, Inc	PDET 31	130627
Programmable AC Source	Chroma	61602	616020002300
Power Analyzer	Xitron	XT2640	2641AD2006004

Test Methods Used:

Title	Description
ANSI C82.77:2002	Harmonic Emission Limits- Related Power Quality Reqt's for Lighting Equipment
CIE Pub.13.3:1995	Method of Measuring and Specifying Color Rendering of Light Sources
CIE Pub.15:2018	Colorimetry
IES LM-58:1994	Spectroradiometric Measurements
ANSI/IES LM-79:2008	Electrical and Photometric Measurements of Solid-State Lighting Products

Reference Standard Used:

Equipment	Description
2M Sphere	Tungsten Halogen Omni-Directional 35W Calibration Lamp, Serial Number E4
Type C Goniophotometer and Spectrometer	Tungsten Halogen Omni-Directional 500W Calibration Lamp, Serial Numbers 16C293, 16C294, 16C295. For color calibration of spectrometer, 13C074.

Disclaimers:

This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST or any agency of the federal government.

The results contained in this report pertain only to the tested sample.

This report shall not be reproduced, except in full, without written approval of the RESTL.

Exceptions:


Data in this report tested under Non-Standard Conditions (i.e. temperature outside the allowed acceptance interval for the equipment/test) are identified with (~).

Data in this report not covered by the NVLAP accreditation, are identified with (*).

In the event testing is subcontracted, subcontracted equipment was used, or performed by the subcontracted laboratory identified in the equipment list of this report, test results in this report marked with the symbol (^).

Additional Comments:

The photos below are intended to show the orientation and fixturing/set-up of the units under test. These are critical to understanding the results of the test given the sensitivity of many products and measurement systems to orientation and set-up considerations, and also for reproducing the conditions of the test.



Document Revision History:







Each subsequent revision of this report replaces the preceding report.

Date	Rev	DCN #	Change at the time of this test	By	Approval
01/04/2024	A	DMS	Origination	M. Hubbard	J. Vollers

ANSI/IES TM-30-18 Color Rendition Report

Source: OSQP-C-3L-57K7-3R-UL (Light Engine)
Date: 1/4/2024

Manufacturer: Cree Lighting
Test: PL18100



Notes:

x 0.3226
y 0.3334
u' 0.2030
v' 0.4721

CIE 13.3-1995
(CRI)
Ra 73
Rg -28