**C-TR-B-BT22-SCCT Series**LED Field Selectable (Lumens and CCT) Basket Troffer | 2' x 2' Replaces up to 4 x F17T8 | 2 x F32T8/U6



# **SELECT YOUR SAVINGS**

With our LED Field Selectable Basket Troffer, easily switch between color temperatures (3500K, 4000K, and 5000K) and lumen packages without having to buy additional fixtures. It delivers up to 5000 or 3750 lumens and features a 5-year limited warranty.



#### PRODUCT SPECIFICATIONS

#### OVERVIEW

- Initial Delivered Lumens: Field Selectable (**50L**: 5000/4550/3750 or **37L**: 3750/3150/2500)
- CRI: ≥ 80
- CCT: Field Selectable Color Temp (3500K/4000K/5000K)
- Input Power: (**50L:** 40W/35W/30W), (**37L:** 30W/25W/20W)
- Dimmable: 0-10V Dimming to 10%

- Operating Temperature Range: -4°F to 104°F (-20°C to 40°C)
- Power Factor: >0.9 at full load
- Total Harmonic Distortion: <20% at full load
- · Limited Warranty: 5-Year\*
- Estimated  $L_{70}$  Lifetime @ 25°C: >100,000 hours
- Replaces up to 4 x F17T8 | 2 x F32T8/U6

FEATURES	RECOMMENDED USE	INPUT VOLTAGE
<ul> <li>Lumen selectable: (50L: 5000/4550/3750) or (37L: 3750/3150/2500)</li> <li>CCT (Color temperature) selectable 3500K/4000K/5000K</li> <li>FCC Part 15, Subpart B, Class A limits for conducted and radiated emissions</li> </ul>	<ul><li> Education</li><li> Retail</li><li> Commercial</li></ul>	<ul> <li>Universal (120V through 277V Operation)</li> <li>*120-347V available</li> </ul>

### **ORDERING INFORMATION**

Example SKU: C-TR-B-BT22-S50L-SCCT-UL-WH-EB

C-TR	В	BT22		SCCT		WH	
PRODUCT	SERIES	STYLE	FIELD SELECTABLE LUMEN PACKAGE	FIELD SELECTABLE CCT	VOLTAGE	HOUSING COLOR	EMERGENCY Backup Option
C-TR	В	BT22 Basket Troffer, 2'x2'	\$50L 5000 Lumens (40W)* 4550 Lumens (35W) 3750 Lumens (30W) \$37L 3750 Lumens (30W)* 3150 Lumens (25W) 2500 Lumens (20W)	SCCT Selectable CCT (Color Temperature) 3500K 4000K* 5000K	UL Universal 120-277V UC *120-347V Opera- tion. Available only with S50L lumen package	<b>WH</b> White	[Blank] w/out Emergency backup option  EB Emergency Backup - Available only with UL voltage - Provides 90 minutes of emergency operation with 1000 lumens

<sup>\*</sup> Default settings at time of shipping are 5000 lumens (S50L) or 3750 lumens (S37L) and 4000K. <sup>‡</sup> UC voltage for Canada only.

#### **CERTIFICATIONS**
















# C-TR-B-BT22-SCCT Series



# **SERIES OVERVIEW**

DIMENSIONS	PRODUCT WEIGHT	MOUNTING HEIGHT	SPACING
(w/out EB): 23-3/4"L x 23-3/4"W x 2-3/4"H	7.7 lbs.	8-12 Feet	8'x 8' - 10'x 10'
(w/EB): 23-3/4"L x 23-3/4"W x 2-3/4"H	8.8 lbs.	8-12 Feet	8'x 8' - 10'x 10'

# **FIXTURE SPECIFICATIONS**

HOUSING	Steel construction, white polyester powder-coat	
LENS ASSEMBLY	Flexible polycarbonate lens	
MOUNTING	Recessed, installs into conventional grid ceilings	

# **ELECTRICAL PERFORMANCE**

OPERATING TEMPERATURE RANGE  ESTIMATED L <sub>70</sub> LIFETIME  @ 25°C (77°F)		POWER FACTOR	TOTAL HARMONIC DISTORTION	
- 4°F to 104°F (-20°C to 40°C) >100,000 Hours		> 0.9 at full load	< 20% at full load	

LUMEN DAOVAGE	FIELD SELECTABLE LUMENS	SYSTEM WATTTS	CURRENT DRAW (AMPS)				
LUMEN PACKAGE	(35K/40K/50K)	(120-277V AND 120-347V)	120V	208V	240V	277V	347V
	5000*	40W	0.33	0.19	0.17	0.14	0.12
S50L	4550	35W	0.29	0.17	0.15	0.13	0.10
	3750	30W	0.25	0.14	0.13	0.11	0.09
	3750*	30W	0.25	0.14	0.13	0.11	N/A
S37L	3150	25W	0.21	0.12	0.10	0.09	N/A
	2500	20W	0.17	0.10	0.08	0.07	N/A



# **C-TR-B-BT22-SCCT Series**

#### **WARRANTY AND CERTIFICATIONS**

WARRANTY	cULus LISTED	DLC
5-Year Limited*	Damp Locations	Premium

## **ACCESSORIES**

DRYWALL GRID ADAPTER
SKU: <b>DGA22-WHT DGA22-WHT-10PK</b> USE: For use when mounting in drywall ceilings

© 2021 Cree Lighting, A company of IDEAL INDUSTRIES. All rights reserved. For informational purposes only. Content is subject to change. Patent www.creelighting.com/patents. C-Lite and the C-Lite logo are registered trademarks of Cree Lighting. The cULus logo is a registered trademark of ULLLC. The DLC QPL logo and the DLC QPL Premium logo are registered trademarks of Northeast Efficiency Partnerships, Inc.

