

C-SW-A Series

LED Stairwell Lighting | Field Selectable CCT and Wattage

Replaces 1-Lamp or 2-Lamp - T5HO 54W



WELL-LIT STAIRWELL LIGHTING AT ITS FINEST

Keep your stairwells well-lit at night with our C-Lite LED Stairwell Lighting. This sleek product features field selectable wattages (35W/50W/60W) and color temperatures (3500K/4000K/5000K). It features a frosted diffuser lens providing reduced glare and excellent light uniformity and an integrated ultrasonic motion sensor. Need one with an emergency battery back up option? We have that too.



PRODUCT SPECIFICATIONS

OVERVIEW

- Max. Delivered Lumens: 7300
- CRI: ≥ 80 CRI
- CCT selectable 3500K/4000K/5000K
- Input Power: 35W/50W/60W
- Factory installed motion sensor comes standard
- Operating Temperature Range: -4°F to 122°F (-20°C to 50°C) **(w/o EB)** | 32°F to 122°F (0°C to 50°C) **(w/ EB)**
- Estimated L₇₀ Lifetime @ 25°C (77°F): >100,000 hours
- Limited Warranty: 5-Year*
- Replaces 1-Lamp or 2-Lamp T5HO fixtures

FEATURES	RECOMMENDED USE	INPUT VOLTAGE
<ul style="list-style-type: none"> • Integrated ultrasonic motion sensor ensures more accurate motion detection compared to microwave sensors • External sensor dip switches provide easy adjustment of dimming level (off, 10%, 25%, 50%), detection sensitivity (low, medium, high) and standby timing (1 min., 5 min., 20 min.) • 150° beam angle • Optional emergency battery backup 	<ul style="list-style-type: none"> • Hallways & Stairways 	<ul style="list-style-type: none"> • Universal (120-347V Operation)

ORDERING INFORMATION

Example SKU: C-SW-A-S66L-SCCT-US-UC-WH-EB

C-SW	A	S66L	SCCT	US	UC	WH	
PRODUCT	SERIES	FIELD SELECTABLE WATTAGE/LUMEN PACKAGE**	FIELD SELECTABLE CCT	MOTION SENSOR	VOLTAGE	HOUSING COLOR	EMERGENCY BACKUP OPTION
C-SW Stairwell Light	A	S66L 7300 Lumens (60W)* / 6175 Lumens (50W) / 4600 Lumens (35W)	SCCT Warm White (3500K)/ Neutral White (4000K)/ Cool White (5000K)*	US Ultrasonic motion sensor	UC 120-347V Operation	WH White	[blank] w/o Emergency backup option EB 8W emergency battery backup driver provides ~1000 lumen output in emergency mode • Suitable for 120-277V only

* Default settings at time of shipping are highest product wattage and 5000K.


** Lumen output at 4000K. Lumen multiplier for 3500K is 0.94 and lumen multiplier for 5000K is 0.97.

CA RESIDENTS WARNING: Cancer and Reproductive Harm –
www.p65warnings.ca.gov

CERTIFICATIONS:



C-SW-A Series



SERIES OVERVIEW

DIMENSIONS	PRODUCT WEIGHT	MOUNTING HEIGHT	SPACING
47-7/8" L x 4-7/8" W x 5-5/8" H	8.03 lbs. (w/o EB)	8 to 10 feet	N/A
	9.13 lbs. (w/EB)		

FIXTURE SPECIFICATIONS

HOUSING	Galvanized steel with a white powder-coat finish
LENS ASSEMBLY	Frosted polycarbonate diffuser lens for superior light uniformity and glare reduction
MOUNTING	Keyhole slots for surface wall mounting. Template included for mounting hole location

LUMINAIRE AND ELECTRICAL PERFORMANCE

OPERATING TEMPERATURE RANGE	ESTIMATED L ₇₀ LIFETIME @ 25°C (77°F)	POWER FACTOR	TOTAL HARMONIC DISTORTION
-4°F to 122°F (-20°C to 50°C) (w/o EB) 32°F to 122°F (0°C to 50°C) (w/ EB)	>100,000 Hours	>0.9 at full load	<25% at full load

REPLACES	LUMEN OUTPUT	SYSTEM WATTS	CURRENT DRAW (AMPS)				
			120V	208V	240V	277V	347V
1 x F54T5HO	7300 Lumens	60W	0.50	0.29	0.25	0.22	0.17
	6175 Lumens	50W	0.42	0.24	0.21	0.18	0.44
	4600 Lumens	35W	0.29	0.17	0.15	0.13	0.1

WARRANTIES AND CERTIFICATIONS

WARRANTY	cULus LISTED
5-Year Limited*	Damp Locations

© 2023 Cree Lighting, A company of IDEAL INDUSTRIES. All rights reserved. For informational purposes only. Content is subject to change. Patent www.creelighting.com/patents. C-Lite and the C-Lite logo are registered trademarks of Cree Lighting. The cULus logo is a registered trademark of UL LLC. The DLC QPL, DLC QPL Premium and the DLC LUNA Logos are the registered and unregistered trademarks of Efficiency Forward, Inc.

US: creelighting.com, e-conolight.com

Distribution/Sales: 855-617-2733 Customer Service: 888-243-9445

Rev. Date: V3 02/01/2023

For informational purposes only. Content is subject to change. *See creelighting.com/resources/warranties for details

C-LITE
LED LIGHTING